

# Spec Sheet

# TexStyles Images

## Sublimation Imaging Fabrics™

Recommended Processes **Dye Sublimation, UV & Latex Inks**

Applications Include; Digital Imaging, Trade Show Banners, Pop Up Displays, Roll Up Banners,

### Key Features of TexStyles Sublimation Imaging Fabrics™ Images

- Wrinkle Resistant
- Exceptional Whiteness
- Vivid Color Reproductions
- Meets all standards coast to coast for flame resistance

TexStyles are stocked in widths 60 & 120 inches. Custom widths available. Contact beaver paper for additional widths that you may require. Standard roll length for TexStyles is 100 yards. Sample rolls are available to ensure suitability for each customers application.

TexStyles Sublimation Imaging Fabrics™		
Physical Property	Standard	Method of Testing
Material	100% Polyester	
Weight	8.5 oz/yd	ASTM D-3776
Width	Various	ASTM D-3774
Tensile Strength - Length	145 (lbf)	ASTM D-5034-09
Tensile Strength - Width	271 (lbf)	ASTM D-5034-09
Elongation - Length	161	ASTM D-5034-09
Elongation - Width	55	ASTM D-5034-09
Lightness	88	CIE L*
Light Transmission / Opaqueness	44%	AATCC 148-1989
Flame Resistance	Passed	NFPA 701-1989
Flame Resistance	Passed	California Code Title 19 1237
Flame Resistance	Passed	NY / NJ Port Authority
Flame Resistance	Passed	Boston City Fire Codes

*Suitability for use is at the sole determination of the user. All values represent averages. Textiles are subject to certain production variances for weight, color, width and physical properties.*

*In order to ensure that the product desired is acceptable, the customer should request a small sample to determine its compatibility for use.*