

# ProTex™

Protection Tissue

## THERMAL TRANSFER TISSUE

ProTex™ tissue's high density, neutral ph and formaldehyde-free composition provides the highest yield and the strongest barrier protection possible. Its heat resistant features extend the life of the calender belt by preventing surplus dye-sub gas from contaminating the belt of the rotary calender press. With more widths and diameters in stock, we have you covered!



### FEATURES AND BENEFITS

#### High tensile strength

Reduces web tear-outs.

#### Wrinkle-free wind

Prevents transferred crease marks.

#### Neutral ph

Retains most tensile strength after prolonged exposure to heat.

#### Recyclable

100% recyclable ingredients.

#### Longer roll lengths

Fewer roll changes, less downtime.

#### Lower basis weight

Reduces purchase transport, storage, and disposal costs.

#### Natural color

No bleaching agents, less harmful to the environment.

#### Formaldehyde free

Eliminates a major cause of heat induced textile yellowing.

#### High gas barrier sheet with heat resistance

Extends the life of the calender belt by blocking excess dye-gas.

### APPLICATIONS

- All heat press calender transfers

# ProTex™ Protection Tissue Properties

Properties	ProTex 19		ProTex 25	
Basis Weight	19 gsm		25 gsm	
Thickness	31.2 µm		44.5 µm	
<b>Thermal Transfer Tissue Approx. Weight Per Roll</b>				
<b>11.5 Pound (19 Gram)</b>				
Roll Widths	16" Diameter	12" Diameter	10" Diameter	8" Diameter
36" (.914 m)	186 lbs.	97 lbs.	69 lbs.	38 lbs.
40" (1.01 m)	207 lbs.	107 lbs.	77 lbs.	42 lbs.
48" (1.21 m)	248 lbs.	129 lbs.	92 lbs.	51 lbs.
54" (1.37 m)	279 lbs.	145 lbs.	104 lbs.	57 lbs.
60" (1.55 m)	311 lbs.	161 lbs.	115 lbs.	63 lbs.
64" (1.63 m)	331 lbs.	172 lbs.	123 lbs.	68 lbs.
66" (1.67 m)	342 lbs.	177 lbs.	127 lbs.	70 lbs.
68" (1.72 m)	351 lbs.	182 lbs.	130 lbs.	72 lbs.
72" (1.83 m)	373 lbs.	193 lbs.	138 lbs.	76 lbs.
80" (2.03 m)	414 lbs.	214 lbs.	153 lbs.	84 lbs.
96" (2.43 m)	497 lbs.	258 lbs.	184 lbs.	101 lbs.
104" (2.64 m)	538 lbs.	278 lbs.	199 lbs.	110 lbs.
Yards per roll	5400 yds.	2800 yds.	2000 yds.	1100 yds.
Feet per roll	16,200 ft.	8,400 ft.	6,000 ft.	16,200 ft.
<b>15 Pound (25 Gram)</b>				
Roll Widths	16" Diameter	12" Diameter	10" Diameter	8" Diameter
126" (3.2 m)	661 lbs.	347 lbs.	244 lbs.	126 lbs.
130" (3.3 m)	680 lbs.	356 lbs.	251 lbs.	129 lbs.
Yards per roll	4200 lbs.	2200 lbs.	1550 lbs.	800 lbs.
Feet per roll	12,600 ft.	6,600 ft.	4,650 ft.	2,400 ft.

## Beaver Paper Headquarters

2420 Tech Center Parkway, Bldg. 140

Lawrenceville, GA 30043 USA

Contact Customer Service & Sales

+1 770-935-5080 x1 | [orders@beaverpaper.com](mailto:orders@beaverpaper.com)

## Beaver Paper GmbH

Im Lossenfeld 19, 77731 Wilstätt Germany

Contact Customer Service

[customerservices@beaverpaper.de](mailto:customerservices@beaverpaper.de)

Authorized Distributor