

# TexPrint<sup>®</sup>MP

## MULTI-PURPOSE DYE-SUBLIMATION PRINT PAPER

TexPrint<sup>®</sup>MP is engineered for the highest-speed, multi-head printers. Easy-to-use, MP's balance of quick-dry coating, excellent dimensional stability, and superb ink drop definition provides the stable performance needed for your printing.



### FEATURES AND BENEFITS

#### High color output

MP's unique blend of coating properties gives you more color, from less ink, than any competing clay and CMC coated sublimation print-sheet.

#### Waste reduction

Available in individually boxed or bulk packaging. Volume users can save time and labor by ordering bulk packaging.

#### Less residual ink

Post printing, MP leaves the least residual ink on the print-page, ensuring the most color applied to your substrate.

#### Quick-Dry coating

MP's quick dry coating provides smudge-free printing, even on the highest-speed printers.

#### More widths and diameters for your applications

Choose the ideal put-up for your print environment. Enjoy less waste, fewer roll changes and more up-time.

#### Energy efficiency

TexPrint<sup>®</sup>MP allows heat to migrate through the print-sheet quicker, reducing calender dwell times and providing higher transfer speed, while delivering the richest and deepest colors.

### APPLICATIONS

- Banners • Blinds • Home Décor • Photography • Signage
- Soft & Hard Surfaces • Trade Show Exhibits

# TexPrint®MP Properties

## TexPrint®MP 95

Basis Weight	95 gsm
Thickness	117 µm
Core I.D.	76 mm / 3"







## Standard Widths

24" / 61.0 cm	•
36" / 91.4 cm	•
44" / 111.8 cm	•
54" / 137.2 cm	•
64" / 162.0 cm	•
75" / 190.0 cm	•
104" / 264.0 cm	•
126" / 320.0 cm	•

## Recommended Printing Conditions: 23-25 °C, 45-55% Humidity

\*TexPrint®MP's hybrid coating combines the efficiency of a CMC coating with the accuracy, definition and quick drying common to clay surface coatings.

GSM	Thickness (µm)	Application	Ink Load	Transfer Efficiency	Ink Drying
95	117				

 Apparel	 Sports Apparel
 Banners/Signage	 Hard Surfaces
 Home Décor	 Fashion

Authorized Distributor

### Beaver Paper Headquarters

2420 Tech Center Parkway, Bldg. 140  
Lawrenceville, GA 30043 USA  
Contact Customer Service & Sales  
☎ +1 770-935-5080 x1 | ✉ orders@beaverpaper.com

### Beaver Paper GmbH

Im Lössenfeld 19, 77731 Wilstätt Germany  
Contact Customer Service  
customerservices@beaverpaper.de

🌐 www.beaverpaper.com ☎ +1 770-935-5080