

TexPrint[®]UT

UTILITY TEXTILE GRADE DYE-SUBLIMATION PRINT PAPER

Easy-to-work-with TexPrint[®]UT papers feature economical ink usage, highest color yields and powerful economics in cost conscious, high-volume textile printing environments. TexPrint[®]UT papers are not designed for hard, smooth, or non-porous substrates.



FEATURES AND BENEFITS

Flatness

TexPrint[®]UT lays flat. Prints flat. Resists cockling even under heavy ink loads. No head strikes, no worries.

Waste reduction

Available in individually boxed or palletized packaging. Volume users can save time and labor by ordering bulk packaging.

Fast ink absorption

Easily keeps pace with the fastest commercial textile printers without offsetting.

Highest dye-gas output

More color, less ink. More color on your fabric and less ink left on your print sheet.

Largest selection of basis weights, widths and roll lengths to mini jumbo

Get exactly the right put-up for your print environment with less waste, fewer roll changes and more up-time.

Faster transfers

TexPrint[®]UT allows heat to migrate through the print sheet quicker, allowing lower calender dwell times and faster transfer speeds, while delivering the richest and deepest dye-gas penetration.




















APPLICATIONS

- Banners • Blinds • Fashion Textiles • Home Décor • Soft Signage
- Textiles • Trade Show Exhibits

TexPrint® UT Properties

| | TexPrint® UT 58 | TexPrint® UT 72 | TexPrint® UT 92-Elite |
|-----------------|-----------------|-----------------|-----------------------|
| Basis Weight | 58 gsm | 72 gsm | 92 gsm |
| Thickness | 75 µm | 88 µm | 110 µm |
| Core I.D. | 76 mm / 3" | 76 mm / 3" | 76 mm / 3" |
| | Standard Widths | | |
| 24" / 61.0 cm | | | ● |
| 36" / 91.4 cm | | ● | ● |
| 44" / 111.8 cm | ● | ● | ● |
| 54" / 137.2 cm | ● | ● | |
| 64" / 162.0 cm | ● | ● | ● |
| 75" / 190.0 cm | ● | ● | ● |
| 104" / 264.0 cm | | | ● |
| 126" / 320.0 cm | ● | ● | ● |

Recommended Printing Conditions: 23-25 °C, 45-55% Humidity

| GSM | Thickness (µm) | Application | Ink Load | Transfer Efficiency | Ink Drying |
|-----|----------------|---|---|--|---|
| 58 | 66 |     |  |  |  |
| 72 | 84 |    |  |  |  |
| 92 | 109 |    |  |  |  |



Apparel



Sports Apparel



Banners/Signage



Hard Surfaces



Home Décor



Fashion

Authorized Distributor

Beaver Paper Headquarters

2420 Tech Center Parkway, Bldg. 140

Lawrenceville, GA 30043 USA

Contact Customer Service & Sales

+1 770-935-5080 x1 | orders@beaverpaper.com

Beaver Paper GmbH

Im Lössenfeld 19, 77731 Wilstätt Germany

Contact Customer Service

customerservices@beaverpaper.de

www.beaverpaper.com +1 770-935-5080