

# TexPrint®XP

## EXTREME PERFORMANCE DYE-SUBLIMATION PRINT PAPER

TexPrint®XP is the original paper that does it all. Excellent for hard surfaces and metal transfers, TexPrint®XP's high-quality consistency and stiffness work together to minimize cockling. XP takes extreme ink-loads while maintaining high definition and color fidelity.

### FEATURES AND BENEFITS

#### Quick-Dry

TexPrint®XP dries fast, eliminating smudges and handling issues.

#### Waste reduction

Available in individually boxed or palletized packaging.

#### Recyclable

Every ingredient in TexPrint®XP is fully recyclable.

#### Versatile

Preferred by professional photographers and exhibit builders, TexPrint®XP works well on both hard and soft substrates.

#### High color yield

More color, less ink. XP leaves the highest color density on your fabric, with less ink left on your print sheet.

#### Largest selection of weights, widths, and roll lengths

With a variety of basis weights, widths up to 3.2 meters and roll lengths to mini jumbo, TexPrint®XP is available in the exact put-up needed for your print environment. Enjoy less waste, fewer roll changes and more up-time.

### APPLICATIONS

- Banners • Blinds • Soft & Hard Surfaces • Home Décor • Photography
- Signage • Trade Show Exhibits

**Recommended printing conditions: 23-25 °C, 45-55% humidity**

GSM	Thickness (µm)	Application	Ink Load	Transfer Efficiency	Ink Drying
105	132	   			
125	150	   			
	Apparel		Sports Apparel		Home Décor
	Banners/Signage		Hard Surfaces		Fashion

## TexPrint®XP Properties

	TexPrint®XP	TexPrint®XP
Basis Weight	105 gsm	125 gsm
Thickness	140 µm	152 µm
Core I.D.	76 mm / 3"	76 mm / 3"
Mini Jumbo Rolls	Yes	yes
Standard Widths		
17" / 43.0 cm	•	
24" / 61.0 cm	•	•
36" / 91.4 cm	•	•
44" / 111.8 cm	•	•
54" / 137.2 cm	•	•
64" / 162.0 cm	•	•
75" / 190.0 cm	•	•
104" / 264.0 cm	•	
126" / 320.0 cm	•	•
Standard 2" Core I.D.		
Core I.D.	51 mm / 2"	
13" X 110', 2" core	•	
13" X 300', 2" core	•	
17" X 110', 2" core	•	
17" X 300', 2" core	•	
24" X 110', 2" core	•	

### Beaver Paper Headquarters

2420 Tech Center Parkway, Bldg. 140

Lawrenceville, GA 30043 USA

Contact Customer Service & Sales

+1 770-935-5080 x1 | [orders@beaverpaper.com](mailto:orders@beaverpaper.com)

### Beaver Paper GmbH

Im Lössenfeld 19, 77731 Wilstätt Germany

Contact Customer Service

[customerservices@beaverpaper.de](mailto:customerservices@beaverpaper.de)

Authorized Distributor